

A red banner with rounded ends is positioned at the top left of the page. It contains the product name in white text.

DS-PDC10DM-EG2-WE Wireless Dual-Tech AM Curtain Detector

- · Slim design for window frame installation
- · IP65 weather resistance for outdoor application
- · Active IR anti-masking
- · Directional detection support
- · Multiple enrollment methods and easy installation
- · Frequency hopping against jamming for reliable transmission



▪ Specification


Model		DS-PDC10DM-EG2-WE
Detection Performance	Detection Method	Passive Infrared, Microwave
	Detection Range	Wall Mount: 10m Ceiling Mount: 5m
	Detection Angle	5°
	Detection Zones	32
	Detectable Speed	0.3~2m/s
	Sensitivity	Auto, Pet
	White Light Filter	6500lux
	Microwave Frequency	24GHz(24.15~24.25GHz)
	Pet Immunity	Wall Mount: 12Kg Ceiling Mount: None
	Digital Temperature Compensation	Support
	Creep Zone Protection	Support
	Anti-masking	Support
Feature	Digital Processing	Support
	Sealed Optics	Support
	Tamper Protection	Front, Rear
	Environment Temperature Indicator	Support
	Signal Strength Indicator	Support
	Directional Detection	Support
Interface	Power Switch	Power Up Enrolling
	LED Indicator	Green(PIR), Red(Microwave), Green+Orange(Mask), Blue(Alarm)
Transmission	Transmission Technology	Tri-X Wireless

	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	868MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	1.6Km
	Frequency Hopping	Support
	Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	Standard Battery Life	5 years in work status (being triggered 20 times per day)
	Power Supply	Battery Powered
	Battery Type	CR123A × 2
	Typical Voltage	3V
General	Operation Temperature	-25 °C to 60 °C (-13°F to 140 °F)
	Storage Temperature	-25 °C to 60 °C (-13 °F to 140 °F)
	Operation Humidity	10% to 90%
	IP Rate	IP65
	Dimension(Wx HxD)	29.2mm × 134.4mm × 39.5mm
	Weight	120g
	Mounting Height	2 to 3.5m
	Mounting Method	Wall,Ceiling
	Application Scenario	Indoor,Outdoor
	Bracket	L-shaped adapter included

▪ **Available Model**

DS-PDC10DM-EG2-WE

Installation





Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com